Technical Specifications

HP Z27 27-inch 4K UHD Display




- 1. Menu
- 2. Viewing Modes
- 3. Information

Front

- 4. Next Active Input
- 5. Power button

Technical Specifications

HP Z27 27-inch 4K UHD Display



- 1. HDMI port
- 2. Mini DisplayPort™
- 3. DisplayPort™
- 4. Audio-out jack

Rear

- 5. USB Type-C™ port (upstream)
- 6. USB Type-A ports (downstream)
- 7. USB Type-A™ port (downstream)
- 8. USB Type-C™ port (downstream)

Technical Specifications

Model: 2TB68A4

Panel Specifications*

Display Size68.58 cm (27")Display Panel TypeIPS with LED backlight

Micro-Edge Bezel Yes, 3-sided

Native Resolution/Timing4K UHD (3840 x 2160 @ 60 Hz) **NOTE:** DisplayPort 1.2 or HDMI 2.0 required to drive panel at its native resolution

Panel Bit Depth 10-bit (8+2 FRC)

Aspect Ratio16:9Brightness - Typical350cd/m2Static Contrast Ratio - Typical1300:1

Dynamic Contrast Ratio (DCR) 5,000,000:1 (Typ.)

Static Contrast Ratio - Minimum 910:1

Pixel Pitch 0.1554 mm x 0.1554 mm

Pixels Per Inch (PPI) 163

Backlight Lamp Life (to half brightness -

in hours)

Anti-Glare Panel Yes

Response Time – Typical 8ms (gray-to-gray)

*Product default is 14ms response time and can be adjusted to as low as 6ms in the display menu. All performance specifications represent the typical specifications provided by HP's component

manufacturers; actual performance may vary either higher

or lower.

178°

30,000 hours minimum

Horizontal Viewing Angle

(typical CR>10)

Vertical Viewing Angle (typical CR>10) 178°

Panel Active Area (w x h) 23.49 x 13.21 in 59.67 x 33.56 cm

Preset Graphic Modes/Supported 640×480 @60Hz Resolutions 720×400 @70Hz

800×600 @60Hz 720×480 @60Hz 1024×768 @60Hz 1280×720 @60Hz 1280×768 @60Hz 1280×800 @60Hz 1280×1024 @60Hz 1440×900 @60Hz 1600×1200 @60Hz 1600×1200 @60Hz 1920×1080 @60Hz 1920×1080 @60Hz 1920×1200 @60Hz 2560×1440 @60Hz 2560×1600 @60Hz

3840×2160 @30Hz 3840×2160 @60Hz

Resolution (native with speed)4K UHD (3840 x 2160 @ 60 Hz)

Maximum Resolution3840 ×2160 @ 60HzRecommended Resolution3840 ×2160 @ 60Hz

Vertical Scan RangeUp to 60 HzHorizontal Scan RangeUp to 135 kHzMaximum Pixel Clock Speed533.25 MHz

Technical Specifications

Color Management

*All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Color Gamut Coverage sRGB 99%

BT.709 100% Factory Color Calibrated Yes

Factory Color Presets BT.709, sRGB D65

Default Color Temperature sRGB D65 **Low Blue Light Modes** Yes

Monitor Exterior Color of Monitor Bezel Black Pearl Specifications

Plug & Play Yes

Tilt Yes, -5 to +23°
Swivel Yes, 90°
Pivot Yes, 90°
Height Adjustment Range Yes, 150 mm

VESA Mounting Yes (one set of standard 4-hole pattern, 100 mm).

Security Lock Ready Yes

Detachable Base Yes, ships detached

Warranty 3/3/0

On Screen Display

(OSD)

On Screen Display User Controls Brightness

Contrast
Color Control
Input Control
Image Control
PIP Control
Power Control
Menu Control
Management
Information
Exit

Monitor Control Buttons or Switches Menu

Viewing Modes Information Next Active Input

Power

User-Assignable Function Buttons Yes. 3

Languages 10 (English, Spanish, German, French, Italian, Netherlands,

Portuguese, Japanese, T-Chinese and S-Chinese)

Connector Types DisplayPort™ 1, DisplayPort™1.2

Mini DisplayPort™ 1, Mini DisplayPort™ 1.2

HDMI 1, HDMI2.0

USB Type-C™ 2, 1 upstream (rear) and 1 downstream (side) **HDCP Support** Yes, HDCP1.4 for DP and HDCP2.2 for HDMI

Audio Output 1, Line out

USB Port USB Version 3.0

USB Hub Yes

Downstream Ports 3 USB-A downstream ports

Fast Charging USB Ports 3 Ports **Power Output Maximum** 7.5W (BC1.2)



Specifications

Technical Specifications

USB-Type	C™	Port
Specificat	ion	5

USB-Type C[™] Version USB 3.1 Gen1 / 5G bps

Downstream USB-Type C™ Ports 1 Port (side) **Upstream USB-Type C™ Ports** 1 Port (rear)

Video Support Rear: USB-C™ Alt mode – DisplayPort™ 1.2 **Power Output** Rear: 5V/3A, 9V/3A, 10V/5A

15V/4.33A, 20V/3.25A Side: 5V/1.5A; 5V/3A Rear: 65W Max

Power Output Maximum Rear: 65\

Side: 15W Max

Special Features

Picture-in-Picture, Picture-by-Picture Remote Manageability

Yes, 2 PIP/PBP No

Power & Operating Specs

Power Supply

Internal

Power Source 100 - 240 VAC 50/60 Hz

Power Consumption – Maximum185WEnergy Saving/Standby Mode0.5WPower Consumption – Typical70WPower cable length1.9 m

ENERGY STAR® Data

Operational Mode at 100 VAC 31.35W
Operational Mode at 115 VAC 31.42W
Operational Mode at 230 VAC 30.51W

EU ENERGY EFFICIENCY CLASS (EC1062)

On-mode Power Consumption (EC

1062/2010)

42W

62 kWh

Annual Power Consumption (EC

1062/2010)

Energy Efficiency Class (EC 1062/2010) B

Ellergy Elliciency class (EC 1002/2010)

Visible Screen Size 27"/68,47 cm Diagonal

Operating Conditions

Operating Temperature - Celsius 5°C to 35°C
Operating Temperature - Fahrenheit 41°F to 95°F
Non-operating Temperature - Celsius -34°C to -60°C
Non-operating Temperature - -29°F to -140°F

Fahrenheit

Operating Humidity 20 - 80% Relative humidity (non-condensing)

Non-operating Humidity 5% - 95%

 $\begin{array}{ll} \textbf{Operating Altitude} & 0-5000m \, (16.400 \, \text{ft.}) \\ \textbf{Non-operating Altitude} & 0-12.192m \, (40.000 \, \text{ft.}) \\ \end{array}$

Environmental Features and Certifications Mercury-free LED display backlighting Yes

Arsenic-Free Display Glass Yes **Low Halogen** Yes

GSE HP-00011-01B, table 2 defines low-halogen (BFR,

CFR. PVC)

NOTE: External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts

obtained after purchase may not be Low Halogen.

Agency Approvals and Certifications WW application

CE,CB,KC/KCC/ICE/TUV-S/ISO 9241-307/ GS/ Low Blue

Light/ BIS/ EAC/ UL/ PSB/ CCC/ CEL/ CECP/ SEPA/TCO/Energy Star/ISC/VCCI/FCC/BSMI/WEEE

Technical Specifications

Microsoft WHQL Certification Win 10, Win 8, Win 7 **ENERGY STAR® Oualified** Yes. ENERY STAR® 7

EPEAT® 2019 Registered Yes

NOTE: Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by

country. Visit http://www.epeat.net for more information. **China Energy Label** CEL Grade 2

TCO Certified Yes

SmartWay Transport Partnership - NA Yes (NA SKU)

only

Contains Recycled Plastics in Back Cover 0.35

Contains Recycled Plastics in 0.35

Base/Stand

Contains Recycled Plastics in Other

Parts

Recyclable Plastics Back cover, Middle cover, VESA cover, Hinge cover, Base

20.7%

top cover, Base bottom cover, Column back cover, Column

front cover

Recyclable Packaging (Box, packing

materials)

Carton, Paper Board, Corner Paper

Unit Product/Package **Specifications**

CONTAINS RECYCLED

PLASTICS

Product Dimensions

Unpacked with stand (W x D x H)

Product Dimensions Packed (W x D x H)

72.4 x 32.2 x 48 cm 61.41 x5.45x36.54cm

Display Head Dimensions Unpacked without stand (W x D x H)

Base Area Footprint

Bezel Measurements Product Weight

Unpacked

Product Weight Packed

Product Weight

(Head Only)

61.41 x23.0x50.98cm 24.18 x9.06x20.07in

28.5 x12.7x18.9in

24.18 x2.23x14.38in

316x230mm 12.44x9.06 in bottom19.27 mm bottom0.76 in

> 20.68lb 9.38kg

11.61kg 25.6lb

6.21kg 13.69lb

Pallet Information Pallet Dimensions

> Metric (L x W x H) Imperial (L x W x H)

Pallet Total Weight Metric (L x W x H)

Imperial (L x W x H) **Pallet Layers**

Documentation

Pallet Product per Laver Container Load, 20-Foot Container Load, 40-Foot Container Load, 40-Foot HighQ 980 x 730 x 120 mm / 1300 x 730 x 120 mm 38.6 x 28.7 x 4.7 in / 51.2 x 28.7 x 4.7 in

> 154.62 kg / 203.26 kg 340.6 lb / 447.7 lb

> > 4 3/4 12/16 224 units

448 units

Software Included **HP Display Assistant**

> AC power cord (1.9m) 6.2 ft USB C-to-A data cable (1.8m) USB-C-to-C cable (1.8m)

DP Cable (1.8m)

What's in the box?

Technical Specifications

User Guide Languages English, Arabic, S. Chinese, T. Chinese, Czech, Danish,

Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

Turkish.

Other Warranty Languages English, Arabic, S. Chinese, T. Chinese, Czech, Danish,

Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

Turkish.

Service and Warranty Protected by HP, including a 3-year standard limited warranty. Optional HP Care Pack Services are

extended service contracts that extend your protection beyond the standard warranties.1



Technical Specifications

Copyright © 2019 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

USB Type-C[™] and USB-C[™] are trademarks of USB Implementers Forum.

ENERGY STAR® is a registered trademark owned by the U.S. Environmental Protection Agency.

1. Care Packs are sold separately. Service levels and response times for HP Care Pack Services may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. See http://www.hp.com/qo/cpc for details.

HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



Technical Specifications

Change Log	
V1 to V2 October 12, 2018	Added USB-C-to-C cable (1.8m)
V2 to V3 May 28, 2019	Updated EPEAT
V3 to v4 May 29, 2019	Updated Response time

